

ZKD1502

Touch Monitor

15" TFT LCD Panel

5 wires touch screen

12V 3A Power adapter



Features

- Taiwan EETI touch card;
- Factory-control Grade A LED panel;
- 24-hour non-stop operation;
- Efficient heat dissipation system;
- Foldable Touch Monitor;
- Support Windows platforms;
- High gloss black edges;
- Support USB touch interface;
- Support VGA input format;
- Multiple installation methods available;
- Integrated touch function and LCD solution.

Specifications

Model	ZKD1502	ZKD1503
Type	15" TFT LCD Panel	15" AUO TFT LCD Panel
Dimension	350*44*275mm (L*W*H)	
Max Resolution	1024×768 @ 60Hz	
Brightness	250cd/m2	
LED Backlight Lifespan	50,000 hours	
Input Voltage	100-240 VAC, 50-60 Hz	
Output Voltage	12 volts at 4 amps max	
Power Consumption	12W(Max)	
Touch Panel Type	Resistive touch (Standard) Capacitive touch (Optional)	Resistive touch from Taiwan Higgstec (Standard) Capacitive touch from Taiwan Higgstec (Optional)

ZKP8001

Thermal Receipt Printer

Fast, Reliable



Features

- Low noise and high-speed printing;
- Support cash drawer driver;
- Low power consumption;
- Low operating costs (No Ribbons or Ink cartridges);
- Built-in data buffers;
- Support different density bitmap graphics printing;
- High-speed printing using embedded;
- soft font for all interfaces;
- Support NV image downloading and printing;
- Support one-dimensional code, two-dimensional code printing.

Specifications

Print Method	Direct Thermal Line Printing
Print Speed	300mm/sec
Print Command	Compatible with ESC/POS
TPH	100 km
Interface(Optional)	Serial/USB/Ethernet/Bluetooth/Wi-Fi
Paper Cutter	Auto Cutter: Full or Partial Cut
Weight	2kg
Dimension	190*145*145mm(L*W*H)
Output (Power Supply)	DC 24V/2.5A
Cash drawer (Power Supply)	DC 24V/1A

ZKB201

Barcode Scanner

2-dimensional barcode scanner

Integrates the lens and decoding function



Features

- Identifying all 1-dimensional bar codes and most 2-dimensional bar codes;
- High Identification ability of barcodes;
- Equipped with four 625±10nm red lights;
- Cursor indicator and the blinking function;
- White and black available, fireproof, waterproof, shock-proof;
- Uses the standard 10-core RJ45 interface;
- Identifying bar codes with low contrast;
- Ultra-long reading Depth of Field (DoF);
- Supports secondary development for various project types.

Specifications

Decode Error Rate	1/8 million
Anti-knock	1.8m free fall to test
Power (Light Source)	< 70mW
Precision	>=4mil
Scan Angle	Rotation: 360°, Tilting: ±50°, Deflection: ±50°
Dimension	163*70*102mm(L*W*H)
Operating Current	130mA
Standby Current	20mA
Maximum Peak	220mA
Voltage	DC3.5V-5.5V(Standard)

ZKC01

Metal Cash Drawer



Specifications

Type	4 Bills, 8 Coins
Check Slots	1 Check Slots
Lock	3 Position Lock
Dimensions	410 mm (W) x 420 mm (L) x 100 mm (H) (excluding rubber feet)
Material	The shell is made of cold-pressed steel plate and the drawer is made of ABS plastic.
Pulse Amplitude	12VDS - 24VDS
Money Clip	Standard Wire Clip
Gross Weight	6.5kg
Net Weight	6.2kg
DC	12V, 24V
Interface	RJ11(Directly connected with receipt printer and cashier interface 12V or 24V)
Color	Black

